

D750 Series

Ku-band Downconverters

INPUT SPECIFICATION		Options
1. Frequency range:	check model table	
2. Connector:	N-type	SMA
3. Impedance:	50Ω	
4. Return loss:	≥20dB	
OUTPUT SPECIFICATION		
5. Frequency range:	check model table	
6. Connector:	BNC	TNC
7. Impedance:	50Ω	75Ω
8. Return loss:	≥15dB	≥20dB (*)
9. 1dB compression point:	+10dBm	
10. Third order intercept:	+20dBm	
TRANSFER CHARACTERISTICS		
11. Gain:	30 to 50dB, adjustable in 0.1dB steps	
12. Gain ripple:	over ±20MHz: ≤1dB p.t.p.	
	over input band: ≤4dB p.t.p.	
13. Group delay distortion:	over ±5MHz <2ns	
	over ±20MHz <5ns	
14. Gain stability, 0°C to 50°C:	±1dB	
15. Frequency stability, 0°C to 50°C:	10 ⁻⁷	Option 2: 10 ⁻⁸ Option 3: 3 x 10 ⁻⁹
16. External reference:	10MHz, 0dBm	5MHz, 0dBm
17. Synthesiser step size:	1kHz	
18. Noise figure (full gain):	<17dB	
Spurii		
19. Image rejection:	>75dB	
20. In-band spurii (at 0dBm output):	<-60dBc	
PHASE NOISE		
21. 10Hz:	<-45dBc/Hz	
22. 100Hz:	<-70dBc/Hz	
23. 1kHz:	<-80dBc/Hz	
24. 10kHz:	<-85dBc/Hz	
25. 100kHz:	<-95dBc/Hz	
26. 1MHz:	<-110dBc/Hz	
27. Mains related:	<-60dBc	
MISCELLANEOUS		
28. Power supply:	115V/230V ±10% 50/60Hz ±10%, 30VA	
29. Mechanical:	1U 19" frame, 400mm deep	
30. Temperature:	Operating: 0° to 50°C	
	Storage: -40° to 85°C	
31. Relative humidity:	Operating: 0 to 90%	
	Storage: 0 to 95%	
32. Summary alarm:	NO and NC dry relay contacts via rear mounted connector	
33. Summary alarm indication:	Front panel LED	
34. Remote control:	<ul style="list-style-type: none"> ● RS232 or RS422/RS485, connector D-type 9P F ● Serial emulation over TCP/IP, connector RJ45 ● SNMP and HTTP over TCP/IP Ethernet, connector RJ45 	

(*) Output compression point and overall gain decrease by 3dB.

MODEL TABLE

Input Frequency	Output frequency and bandwidth		
	70 ± 20MHz	140 ± 40MHz	70 ± 20MHz, 140 ± 20MHz and ±40MHz
10.95 - 11.7GHz	D750	D755	D770
11.7 - 12.25GHz	D751	D756	D771
12.25 - 12.75GHz	D752	D757	D772
10.7 - 12.75GHz	D753	D758	D773
10.7 - 11.7GHz	D754	D759	D774
12.75 - 13,25GHz	D791		
13.75 - 14.50GHz			